

- Low installation costs with easy mounting
- Light weight
- Compact body
- Durable material

## Features

**Material:** Float- 316SS

Guide Rod: 316SS

Body: Clear Acrylic

Thread: Brass or Plastic

**Thread:** 1/8", 1/4", 3/8", 1/2", 3/4", 1"

**Temperature limit:** 60°C Maximum

**Accuracy:** ±4% full scale



Model	Media	Flow Rate	Thread Size
FMV 03	Water	1-12 LPM	1/8" BSP
FMV 06	Water	2-25 LPM	1/4" BSP
		4-40 LPM	1/4" BSP
FMV 15	Water	2-20 LPM	1/2" BSP
FMV 20	Water	4-38 LPM	3/4" BSP
FMV 25	Water	5-35 LPM	1" BSP
		20-70 LPM	1" BSP
		30-100 LPM	1" BSP
FMVA	Air	0.2-2 LPM	1/4" BSP
		0.4-5 LPM	1/4" BSP
		3-35 LPM	1/4" BSP
FMVA 10	Air	0.2-2 LPM	3/8" BSP
FMVA 15	Air	0.6-6m <sup>3</sup> /Hr	1/2" BSP

*Other flow rates and thread combinations available, please contact us for more information  
Weight and dimensions available upon request.*